

WISI VS 95

Split band amplifier



Description

split band amplifier to after amplifier terrestrial and 2 SAT frequency bands on two trunk line.

Technical data

SAT-IF

Inputs SAT	2 pcs. (via filter)
Frequency range SAT	950...2150 MHz
Gain SAT	29...32 dB
Attenuator SAT	20 dB
Equalizer SAT	7 dB (switchable)
Output level SAT	106 dB
Noise figure SAT	6 dB

terrestrial

Inputs TERR	2 pcs. (via filter)
Frequency range TERR	47...862 MHz
Gain TERR	23...29 dB
Attenuator TERR	20 dB
Equalizer TERR	6 dB (switchable)
Output level TERR	117 dB μ V

Connectors

F-socket	4 pcs.
----------	--------

General data

Operating voltage AC	230 V
Power consumption	9 W
LNB supply voltage	0 V
LNB electrical power supply	- A
EMC	Class A, EN 50083-2
Dimensions (width x height x depth)	177x122x40 mm
Operating temperature range	-10...+50 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	197 x 230 x 75 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.250 kg
Shipping unit	5 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	3.4 dm ³
Gross weight shipping unit	1.25 kg
EAN	4010056130053
Article number	13005
Customs tariff number	85437030